

B-RAD S



DISPLAY

The torque wrench with the highest accuracy on the market


Equipped with a built-in transducer, the B-RAD S makes logging torque output easier and more efficient than ever with its ability to read and display torque in real time. The transducer enables the B-RAD S to audit previously tightened bolts - accurately measuring the applied torque and creating zero risk of an over-torque. The B-RAD S includes Bluetooth connectivity, torque and angle operation, and automatic release of the reaction arm to minimize your downtime and maximize your torque output.

FEATURES

- Torque range up to 5,000 ft. lbs./ 7,000 Nm
- New and improved battery life
- Bolt counter
- Brushless motor
- Password protection

CASE

Durable, light weight, shock proof. Designed to protect your RAD investment.



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW	TORQUE (ft. lbs.) HIGH	RPM	WEIGHT (lbs.)	NOISE LEVEL	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
31800	B-RAD S 500	0.75"	50	500	21	9.2	85	12.25"	2.48"	2.75"	10"
31802	B-RAD S 1000	0.75"	100	1000	9.6	9.4	85	12.25"	2.48"	2.75"	10"
31804	B-RAD S 1500	1.0"	150	1500	5.6	10.8	85	12.63"	2.7"	2.75"	10"
31806	B-RAD S 3000	1.0"	300	3000	3	15.9	85	13.25"	3.18"	3.18"	10.13"
31808	B-RAD S 5000	1.5"	500	5000	1.9	21.7	85	14.25"	3.74"	3.74"	10.5"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM	WEIGHT (Kg)	NOISE LEVEL	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
31801	B-RAD S 700	0.75"	70	700	21	4.2	85	311	63	70	254
31803	B-RAD S 1400	0.75"	135	1400	9.6	4.3	85	311	63	70	254
31805	B-RAD S 2000	1.0"	200	2000	5.6	4.9	85	321	69	70	254
31807	B-RAD S 4000	1.0"	400	4000	3.0	7.2	85	337	81	81	257
31809	B-RAD S 7000	1.5"	700	7000	1.9	9.8	85	362	95	95	267

Accuracy of +/-5%, Repeatability of +/-2%