

# RAD SINGLE SPEED



WARNING: AIR PRESSURE  
IS PROVIDED FOR YOUR  
PROTECTION. ALWAYS  
WEAR EYE PROTECTION.  
DO NOT OPERATE THIS  
TOOL WITHOUT PROPER  
TRAINING. ALWAYS  
USE PROPER  
OPERATING  
TECHNIQUE.  
DO NOT  
OPERATE  
THIS  
TOOL  
IF YOU  
ARE  
DRIVING  
OR  
OPERATING  
MACHINERY.  
DO NOT  
OPERATE  
THIS  
TOOL  
IF YOU  
ARE  
DRIVING  
OR  
OPERATING  
MACHINERY.  
DO NOT  
OPERATE  
THIS  
TOOL  
IF YOU  
ARE  
DRIVING  
OR  
OPERATING  
MACHINERY.

**RAD**  
TRUCK SYSTEM  
RED 150X  
www.radusa.com

# Extreme duty torque wrenches for heavy duty applications

PNEUMATIC




30 years of experience in gearbox engineering and design has brought about our latest generation in planetary gearboxes – RAD Single Speed. Designed for extreme duty use in a variety of industries worldwide, RAD Single Speed torque wrenches offer:

## FEATURES

- The ultimate in power-to-weight ratio
- Wide torque range to suit multiple applications
- Unmatched reliability delivered by one of the most advanced engineered gear boxes on the market
- Controlled torque - accuracy of +/- 4% and repeatability of +/- 2%

## FRL UNIT

- Low weight tool holder made from high-density polypropylene
- Includes pressure gauge, filter, regulator and oiler



## IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW HIGH	RPM	WEIGHT (lbs.)	NOISE LEVEL	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
12316	RAD 350SL	0.75"	50 350	65	6	80 db	6.6"	2.4"	2.75"	8.75"
12814	RAD 7GX	0.75"	100 700	30	8	80 db	9.0"	2.5"	2.75"	9.0"
12818	RAD 10GX	0.75"	200 1000	20	8	80 db	8.15"	2.5"	2.75"	8.07"
17328	RAD 15DX	1.0"	300 1500	10	8.6	80 db	8.0"	2.7"	2.75"	8.1"
12377	RAD 25GX	1.0"	500 2500	9	13.5	85 db	9.7"	3.1"	3.3"	9.5"
22238	RAD 30DX	1.0"	900 3000	8	14.8	85 db	10"	3.2"	3.3"	9.5"
12356	RAD 34GX*	1.0"	1000 3400	12	20	85 db	12.5"	3.4"	3.7"	10.8"
20248	RAD 50DX	1.5"	1500 5000	6.7	23.5	85 db	11.25"	3.75"	3.75"	10.4"
15328	RAD 60DX	1.5"	2000 6000	6.6	27.6	85 db	13.7"	4.0"	4.0"	10.9"
18558	RAD 80DX	1.5"	2500 8000	4	30.5	85 db	12.15"	4.25"	4.25"	10.65"
26152	RAD 110DX	1.5"	4000 11000	3	42	85 db	13.9"	5.0"	5.0"	11.07"

## METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW HIGH	RPM	WEIGHT (Kg)	NOISE LEVEL	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
13573	RAD 475SL-M	0.75"	70 475	65	2.7	80 db	167	61	70	222
13539	RAD 10GX-M	0.75"	150 950	30	3.6	80 db	228	63	70	228
13549	RAD 14GX-M	0.75"	275 1400	20	3.8	80 db	228	63	70	228
19135	RAD 20DX-M	1.0"	400 2000	10	4.0	80 db	203	69	70	228
13565	RAD 34GX-M	1.0"	700 3400	9	6.1	85 db	240	78	83	241
24717	RAD 40DX-M	1.0"	1200 4000	8	6.7	85 db	254	81	83	241
13571	RAD 46GX-M*	1.0"	1400 4600	12	9.0	85 db	317	86	94	274
26133	RAD 70DX-M	1.5"	2000 7000	6.7	10.6	85 db	285	95	95	264
15805	RAD 80DX-M	1.5"	2700 8000	6.6	12.4	85 db	348	101	101	276
23229	RAD 110DX-M	1.5"	3400 11000	4	13.7	85 db	308	108	108	270
26153	RAD 150DX-M	1.5"	5500 15000	3	18.9	85 db	353	127	127	281

Accuracy of +/-4%, Repeatability of +/-2% | \*Also available in a 1.5" square drive.



## ADVANCED BOLTING SOLUTIONS PVT. LTD.

HO: "ABS House", Plot No. W-116 (A),  
T.T.C. Industrial Area, MIDC Khairane,  
Navi Mumbai - 400 710.

Tel: +91 22 3526 4444  
E-mail: sales@absgroup.in  
Web: www.absgroup.in