

# B-RAD XTREME

**NEW!**



DISPLAY

**CASE**

Durable, light weight, shock proof. Designed to protect your RAD investment.



# All New Tool with Extreme Battery-Powered Torque!

BATTERY



The all-new B-RAD Xtreme (B-RAD X) raises the bar for torque range capacity with a battery tool, maxing out at an impressive 11,000 ft. lbs./ 15,000 Nm. – making the B-RAD X officially the biggest cordless torque tool on the market. Plus, with 4% accuracy this tool will stand up to the toughest scrutiny. The B-RAD X captures attention with its sleek new white design and rubber handle paired with RAD Torque's patented and world-renowned gearbox technology.

## MODELS

- B-RAD X 5,000 ft. lbs./ 7,000 Nm
- B-RAD X 8,000 ft. lbs./ 10,000 Nm
- B-RAD X 11,000 ft. lbs./ 15,000 Nm

## FEATURES

- Brushless DC motor for added durability and accuracy
- Redesigned anti-fatigue trigger switch
- Standard hand-guard for added operator protection
- Two-hand start options to prevent hand injuries
- Battery latch lock to protect batteries from falling
- 4-button interface with high-contrast LED display provides feedback during operation.

## ACCESSORIES



### SOFT SLING

Great for horizontal or vertical applications and allows the tool to easily pivot between these two orientations.




### TOP HANDLE

The top handle is intended for horizontal applications, or applications that can tolerate the extra envelope this adds to the tool.



### REAR HANDLE

The rear handle is intended for vertical applications, or for use in conjunction with the sling in horizontal applications to provide a better leverage point over just the handle by itself.



## IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (FT LBS) LOW	TORQUE (FT LBS) HIGH	RPM	WEIGHT (lbs)	DIMENSION A (in)	DIMENSION B (in)	DIMENSION C (in)	DIMENSION D (in)
30656	B-RAD X 5000	1.5"	500	5000	2.4	23	12.5	3.75	3.75	14.25
30658	B-RAD X 8000	1.5"	740	8000	1.7	30	13.75	4.25	4.25	14.5
30660	B-RAD X 11K*	1.5"	1100	11000	1.2	42	15.25	5	5	14.75

## METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
30657	B-RAD X 7000-M	1.5"	700	7000	2.4	10.5	318	95	95	362
30659	B-RAD X 10K-M	1.5"	1000	10850	1.7	13.8	349	108	108	369
30661	B-RAD X 15K-M*	1.5"	1500	15000	1.2	19.3	387	127	127	375

Accuracy of +/-4%, Repeatability of +/-2% | \*Also available in a 2.5" square drive.



### ADVANCED BOLTING SOLUTIONS PVT. LTD.

HO: "ABS House", Plot No. W-116 (A),  
T.T.C. Industrial Area, MIDC Khairane,  
Navi Mumbai - 400 710.

Tel: +91 22 3526 4444  
E-mail: sales@absgroup.in  
Web: www.absgroup.in