

# E-RAD BLU-S



## CASE

Durable, light weight, shock proof. Designed to protect your RAD investment.

## SOFT SLING

Great for horizontal or vertical applications and allows the tool to easily pivot between these two orientations.

# Supreme Transducer Technology with High Accuracy

ELECTRONIC



The integrated transducer measures torque output in real time, ensuring the tool stops precisely where it needs to. This feedback loop allows the E-RAD BLU-S to operate accurately regardless of the joint condition and will even allow you to check a previously tightened bolt without applying too much torque.

## FEATURES

- Built-in transducer
- Advanced data logging and tool management features
- Password protection on three user levels: basic, intermediate, and advanced
- Operator identification ensures traceability of each torque sequence performed
- Capable of torque and angle bolting sequence
- LED indicator lights (pass/fail)
- Extremely low noise level at only 75dB


## TOUCH CONTROL CASE

- Easy to use interface
- Pre-sets for torque and angle adjustments
- Quick error-free torque and angle adjustments
- Complete recalibrations
- Data logging with export to laptop



## RAD SMART SOCKETS™

RAD SMART SOCKETS™ can connect to the E-RAD BLU tool via Bluetooth® technology. This combination allows you to automatically calibrate your E-RAD BLU to any joint!



## IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW HIGH	RPM 120V 230V	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
30079	E-RAD BLU-S 700	0.75"	100 700	15 30	13	14.96"	2.84"	3.03"	10.65"
28836	E-RAD BLU-S 2500 COMP	1.0"	250 2500	5 10	19	16.21"	3.41"	3.03"	10.65"
31190	E-RAD BLU-S 3000	1.0"	500 3000	5 10	24.5	17.76"	3.73"	3.48"	11.29"
31191	E-RAD BLU-S 6000	1.5"	1000 6000	2.1 4.5	30	17.71"	4.35"	3.48"	11.29"
31192	E-RAD BLU-S 7500	1.5"	1500 8000	1.5 3	34	18.53"	4.48"	3.48"	11.29"
29314	E-RAD BLU-S 11K*	1.5"	3000 11000	1.5 2.3	44	19.81"	5.21"	3.48"	11.29"

## METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW HIGH	RPM 120V 230V	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
26937	E-RAD BLU-S 950-M	0.75"	135 950	15 30	5.9	380	72	77	270.5
26938	E-RAD BLU 3400-S-M COMP	1.0"	340 3400	5 10	8.6	412	87	77	270.5
22759	E-RAD BLU-S 4000-M	1.0"	675 4000	5 10	11.1	451	95	88	287
25282	E-RAD BLU-S 8000-M	1.5"	1350 8100	2.1 4.5	13.6	450	110.5	88	287
26939	E-RAD BLU-S 10K-M	1.5"	2000 10000	1.5 3	15.4	471	114	88	287
29315	E-RAD BLU-S 15K-M*	1.5"	4050 15000	1.5 2.3	20	503	132	88	287

Accuracy of +/- 2.8%, Repeatability of +/- 2% | \*Also available in a 2.5" square drive.



## ADVANCED BOLTING SOLUTIONS PVT. LTD.

HO: "ABS House", Plot No. W-116 (A),  
T.T.C. Industrial Area, MIDC Khairane,  
Navi Mumbai - 400 710.

Tel: +91 22 3526 4444  
E-mail: sales@absgroup.in  
Web: www.absgroup.in