

RAD HIGH SPEED



Extreme duty torque wrenches with high RPM productivity

PNEUMATIC



Looking for high RPM productivity? RAD High Speed torque wrenches incorporate a precision-engineered, high-speed gearbox designed for faster run down and quick reaction point positioning on time sensitive bolting applications.

The two-speed models feature a unique fully automatic gearbox design, eliminating the time-consuming switch between high and low speed gear.

FEATURES

- The ultimate in power-to-weight ratio
- Wide torque range to suit multiple applications
- Unmatched reliability delivered by one of the most advanced engineered gear boxes on the market
- Controlled torque accuracy of +/- 4% and repeatability of +/- 2%


FRL UNIT

- Low weight tool holder made from high-density polypropylene
- Includes pressure gauge, filter, regulator and oiler



IMPERIAL

| PART NUMBER | TOOL MODEL | DRIVE SIZE | TORQUE LOW | TORQUE (ft. lbs.) HIGH | RPM | WEIGHT (lbs.) | NOISE LEVEL | DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|-------------|------------|------------|------------|------------------------|-----|---------------|-------------|-------------|-------------|-------------|-------------|
| 10644 | RAD 10GX-2 | 0.75" | 350 | 1000 | 85 | 9.9 | 80 db | 10.3" | 2.5" | 2.75" | 8.1" |
| 17068 | RAD 15DX-2 | 1.0" | 500 | 1500 | 50 | 10.5 | 80 db | 9.9" | 2.7" | 2.75" | 8.1" |
| 19773 | RAD 25GX-2 | 1.0" | 700 | 2500 | 44 | 16.6 | 80 db | 12.0" | 3.1" | 3.3" | 10.0" |
| 24950 | RAD 30DX-2 | 1.0" | 1000 | 3000 | 49 | 16.1 | 80 db | 12.2" | 3.2" | 2.75" | 9.5" |



METRIC

| PART NUMBER | TOOL MODEL | DRIVE SIZE | TORQUE (N m) LOW | TORQUE (N m) HIGH | RPM | WEIGHT (kg) | NOISE LEVEL | DIMENSION A (mm) | DIMENSION B (mm) | DIMENSION C (mm) | DIMENSION D (mm) |
|-------------|--------------|------------|------------------|-------------------|-----|-------------|-------------|------------------|------------------|------------------|------------------|
| 19774 | RAD 14GX-2-M | 0.75" | 475 | 1400 | 85 | 4.5 | 80 db | 261 | 63 | 70 | 205 |
| 19775 | RAD 20DX-2-M | 1.0" | 700 | 2000 | 50 | 4.7 | 80 db | 251 | 68 | 70 | 205 |
| 19776 | RAD 34GX-2-M | 1.0" | 950 | 3400 | 44 | 7.5 | 80 db | 305 | 78 | 84 | 254 |
| 24952 | RAD 40DX-2-M | 1.0" | 1400 | 4000 | 49 | 7.3 | 80 db | 309 | 81 | 83 | 254 |

Accuracy of +/-4%, Repeatability of +/-2%

ADVANCED BOLTING SOLUTIONS PVT. LTD.

ABS House, W-116 (A), T.T.C. Industrial Area,
MIDC Khairane, Navi Mumbai - 400 710.

Phone: +91 82828 29795
Email: marketing@absgroup.in

www.absgroup.in

